



MINIATURIZED SCALE GREEN GROWTH GATHERED FROM THE INDIAN LAKES UTILIZED TO DERIVE THE BIO-DIESEL

**TEJDEEP REDDYKALLAM, B. NAGESWARA RAO* and
ARADHYULA TIRUMALA VASU**

Department of Mechanical Engineering, VFSTR University, GUNTUR – 522213 (A.P.) INDIA

ABSTRACT

Microalgae are alternative source for biodiesel production due to the prospective high oil content in its cells and fast generation to yield a higher biomass. The focus of the study was to provide a feasibility study on the potential of a local isolated strain for biodiesel production comprising of cell growth, micro algae from the local ponds, which are grown in tubs at laboratory by open pond cultivation system with addition of nutrients to it, the grown algae dried under shade dry, weigh the amount of dried powder and extracted for the oils in the culture for the production of biodiesel, The dried sample was weighed and the sample was in extracted in Soxhlet extractor with the help of the solvents like n-hexane, chloroform and methanol (2:1) ratio. The solvents dissolved in lipped extract was evaporated by rotator evaporation system. Lipped extract remains in it eventually by transesterification, the pure biodiesel was obtained.

Key words: Growth, Light, Lipid, Microalgae, Renewable energy.

INTRODUCTION

Vitality deficiency, taking off oil costs, and environmental change empower the innovative work of option vitality assets to manage financial development. Biofuel, for example, biodiesel and biomass-based liquor fills are case of such options. The methyl esters of vegetable oils, known as biodiesel are turning out to be progressively famous due to their low natural effect and potential as a green option fuel for diesel motor and they would not require critical adjustment of existing motor equipment.

The over utilization of these fills has depleted these characteristic assets and expanded the centralization of nursery gasses, which has conveyed negative effect to the earth and

* Author for correspondence; E-mail: tejdeep666@gmail.com, nag4mech@gmail.com, aradhyulaturumalavas@gmail.com

human life. Every year, human exercises have added to the expansion in the level of carbon dioxide (CO₂) in the climate where 33% of the CO₂ radiated is consumed by the sea. As the measure of broke down CO₂ builds, it will raise the acidity of the sea's pH. Acidic pH may instigate quick loss of coral reefs and marine biological systems biodiversity while bringing about gigantic ramifications to sea life and therefore in earth life. Furthermore, worry on vitality security, environmental change and taking off oil costs which have spreaded quickly in the 21st century, is driving policymakers and researchers to scan for ecologically amicable, financially aggressive and net vitality positive fills. Biodiesel which is a biodegradable and non-poisonous fuel has increased much consideration as of late because of its eco-accommodating nature since it has lower net carbon cycle contrasted with traditional diesel powers. Furthermore, biodiesel can be utilized with negligible or no alterations in diesel motors because of its nearby similarity in the physicochemical properties with petroleum diesel. By and large, biodiesel is delivered from creature fats, vegetable oils or reused cooking oil by synthetically responding them with liquor. The procedure is known as transesterification.

EXPERIMENTAL

Material and methods

Miniaturized scale green growth from the neighborhood lakes which are developed in tubs at lab by open lake development framework with option of supplements to it (Glucose (1 g/L), potassium dihydrogen phosphate (5 g/L), di potassium hydrogen phosphate (5 g/L), sodium nitrate (5 g/L), and other follow metals (0.5 g/L)), The supplements are added to it enough, which are required for the development of green growth and screen the levels of water in tubs day by day and keep up it for two weeks and look at the biomass of the developed green growth and ordinary lake green growth. The developed green growth dried under shade dry, dried powder was measured and extricated for the oils in the way of life for the creation of biodiesel, The dried example was weighed and the specimen was removed separated in Soxhelt extractor with the assistance of the solvents like n-hexane, chloroform and methanol (2:1) proportion. The whole setup was keep running for 10 cycles and henceforth at long last, we could get solvents with lipped concentrate. The solvents broke down in concentrate was dissipated by rotator vanishing framework lipped concentrate stays in it.

The lipid extricated was blended with 0.25 g immaculate sodium hydroxide beds and 24 mL methanol for 20 min. The blend was kept in a hatchery shaker at 45-50°C and mixed at 300 rpm for 3 hrs. In the wake of shaking, the arrangement was kept for 16 hrs in a separatory channel to settle the biodiesel and silt layers obviously. The silt which comprised

of glycerine, shades and others were disposed off and the biodiesel was washed with 5% water until it turned out to be clear. The biodiesel was then dried utilizing dryer and kept under running fan for 12 hrs. The biodiesel was then put away for examination. The properties of biodiesel, for example, thickness, kinematic consistency, streak point and fire point were resolved.

RESULTS AND DISCUSSION

Natural parameters, for example, pH, biomass adds to the green growth refined procedure. These parameters discover the development rate of green growth. In the first place, the cooperation's amongst pH and biomass. It was found that there were develop rate between typical lake green growth and developed pH and biomass at three distinctive levels as delineated. Consequently, the individual impact of these parameters on biomass yield was explored broadly in this work.

The fuel properties required are streak point, fire point, thickness and kinematic consistency, all are resolved.

Biomass distinction between typical lake green growth and developed green growth

The heaviness of the lake green growth is 500 g, which is isolated creamer put in two tub and the procedure of supplements expansion to tub 1 and tub 2 has no supplements expansion as shown in Table 1. The values taken per every two days, the biomass in tub 1 is 250, 263, 275, 281, 291, 305 and 320, the biomass in tub 2 250, 250, 255, 256, 258, 256 and 259 and finally the bio mass difference between tub 1 and tub 2 is 0, 13, 20, 26, 32, 49 and 63.

Table 1: The biomass difference between tub1 and tub 2

S. No.	Nutrients gram/Liter	Tub 1 Algae weight (grams)	Tub 2 Algae weight (grams)	Weight in difference (grams)	Number of days
1	10/40	250	250	0	2
2	10/40	263	250	13	4
3	10/40	275	255	20	6
4	10/40	281	256	26	8
5	10/40	291	258	32	10
6	10/40	305	256	49	12
7	10/40	320	259	61	14

pH contrast between ordinary lake green growth and developed green growth

The pH estimations of tub 1 and tub 2 are resolved per at regular intervals the outcomes as appeared in Table 2

Table 1: The pH difference between tub 1 and tub 2

S. No.	Number of days	Tub 1 pH	Tub 2 pH	pH Difference
1	2	6.9	6.9	0
2	4	7.1	7.0	0.1
3	6	7.2	7.1	0.2
4	8	7.3	7.3	0
5	10	7.6	7.3	0.6
6	12	7.9	7.5	0.4
7	14	7.9	7.6	0.3

As shown in Table 1, the values taken per every two days, the pH in tub 1 is 6.9, 7.1, 7.2, 7.3, 7.6, 7.9 and 7.9, and in tub 6.9, 7, 7.1, 7.3, 7.3, 7.5 and 7.6 and finally the pH difference between tub 1 and tub 2 is 0, 0.1, 0.2, 0, 0.6, 0.4 and 0.3.

Fuel properties are also measured (Table 3). They are kinematic consistency, streak point and fire point at various mixing proportions like B0, B10 and B20.

Table 3: properties of Fuel at different blending ratios

S. No.	Incorporation ratios	Kinematic viscosity incentistokes	Flash point (°C)	Fire point (°C)
1	0% Bio diesel oil in diesel	1.1	59	71
2	10% Bio diesel oil in diesel	1.2	62	74
3	20% Bio diesel in diesel	1.4	65	75

The kinematic viscosity of B0, B10 and B20 are 1.1, 1.2 and 1.4, respectively, flash point for B0, B10 and B20 are 59, 62 and 65 respectively and fire point for B0, B10 and B20 are 71, 74 and 74, respectively.

CONCLUSION

The motor execution of biodiesel mixes with diesel at various proportions 100%-0%, 90%-10%, 80%-20%. Selected mixtures were examined and the outcomes contrasted and unadulterated diesel and reported in this paper. The outcomes are demonstrating that all the fuel properties are greatly recommended at B20. The biomass of the green growth likewise expanding by including supplements is 63 g expanded for 250 g of green growth with in 14 days.

REFERENCES

1. S. Suranovic, Fossil Fuel Addiction and the Implications for Climate Change Policy, *Global Environ. Change-Human Policy Dimen.*, **23(3)**, 598-608 (2013).
2. G. Fioerese, M. Catenacci, V. Bosetti and E. Verdolini, The Power of Biomass: Experts Disclose the Potential for Success of Bioenergy Technologies, *Energy Policy* (2013).
3. L. Di Lucia, Too Difficult to Govern? An Assessment of the Governability of Transport Biofuels in the EU. *Energy Policy*, **63**, 81-88 (2013).
4. S. Baier, M. Clements, C. Griffiths and J. Ihrig, Biofuels Impact on Crop and Food Prices: Using an Interactive Spreadsheet, in *International Finance Discussion Papers*, Board of Governors of the Federal Reserve System (2009).
5. D. Pimentel and M. Pimentel, Corn and Cellulosic Ethanol Cause Major Problems, *Energies*, **1(1)**, 35-37 (2008).
6. G. Fiorese, M. Catenacci, E. Verdolini and V. Bosetti, Advanced Biofuels: Future Perspectives from an Expert Elicitation Survey, *Energy Policy*, **56**, 293-311 (2013).
7. A. F. Clarens, H. Nassau, E. P. Resurreccion, M. A. White and L. M. Colosi, Environmental Impacts of Algae-Derived Biodiesel and Bioelectricity for Transportation, *Environ. Sci. Technol.*, **45(17)**, 7554-7560 (2011).
8. P. M. Schenk, S. R. Thomas-Hall, E. Stephens, U. C. Marx, J. H. Mussgnug, C. Posten, O. Kruse and B. Hankamer, Second Generation Biofuels: High-Efficiency Microalgae for Biodiesel Production, *Bioenergy Res.*, **1(1)**, 20-43 (2008).
9. N. K. Singh and D. W. Dhar, Microalgae as Second Generation Biofuel, A review, *Agrono. Sustain. Develop.*, **31(4)**, 605-629 (2011).
10. Y. Chisti and J. Y. Yan, Energy from Algae: Current Status and Future Trends, *Algal Biofuels - A Status Report*, *Appl. Energy*, **88(10)**, 3277-3279 (2011).

11. J. Sheehan, T. Dunahay, J. Benemann and P. Roessler, A Look Back at the U.S. Department of Energy's Aquatic Species Program-Biodiesel from Algae., National Renewable Energy Laboratory (1998).
12. J. H. Ryther, T. A. DeBusk and M. Blakeslee, Cultivation and Conversion of Marine Macroalgae, Solar Energy Research Institute: Colorado (1984).
13. W. J. Oswald, A. A. M., H. B. Gotaas and M. Asce, Photosynthesis in Sewage Treatment, Am. Soc. Civil Eng. (1955).
14. C. G. Golueke, , W. J. Oswald and H. B. Gotaas, Anaerobic Digestion of Algae, Appl. Microbiol., **5(1)**, 47-55 (1957).
15. M. Uziel, Solar Energy Fixation and Conversion with Algal Bacterial Systems, University California Berkeley: Berkeley (1978).
16. T. Bruton, H. Lyons, Y. Lerat, M. Stanley and M. Bo Rasmussen, A Review of the Potential of Marine Algae as a Source of Biofuel in Ireland, Sustainable Energy Ireland: Dublin, Ireland (2009).
17. A. Zidansek, R. Blinc, A. Jeglic, S. Kabashi, S. Bekteshi and I. Slaus, Climate Changes, Biofuels and the Sustainable Future, Int. J. Hydrogen Energy, **34(16)**, 6980-6995 (2009).
18. L. Rosgaard, A. J. de Porcellinis, J. H. Jacobsen, N. U. Frigaard and Y. Sakuragi, Bioengineering of Carbon Fixation, Biofuels, and Biochemicals Incyanobacteria and Plants, J. Biotechnol., **162(1)**, 134-147 (2012).

Accepted : 10.07.2016