

Nano Science and Nano Technology

An Indian Journal

📼 Full Paper

NSNTAIJ, 10(1), 2016 [001-006]

Microwave-assisted synthesis of silver doped with cadmium sulphide using capping agent

C.Selvakumar^{1*}, M.Deepa² ¹Research and Development Centre, Bharathiar University, Coimbatore, (INDIA) ²Department of Chemistry, Muthurangam Arts and Science College, Vellore, (INDIA) E-mail : cselva1984@gmail.com

ABSTRACT

Silver doped Cadmium Sulphide nanoparticles were synthesized at room temperature using Microwave assisted method with various molecular ratio. The size of nanometer particles nearly 5nm were controlled by using poly vinyl alcohol as a capping agent. The nanoparticles size and morphology was studied by using FTIR, Scanning electron microscope, Transmission electron microscope, Energy Dispersion X-ray analysis and XRD. © 2016 Trade Science Inc. - INDIA

KEYWORDS

Microwave-Assisted; Capping agent; Molecular ratio; Silver doped with Cadmium Sulphide.

INTRODUCTION

The development of uniform nano meter sized particles has been intensively pursued because of their technological and fundamental scientific importance^[1,2]. These Nano particulates materials often exhibit very interesting electrical, optical, magnetic, and chemical properties, which cannot be achieved by their bulk counter parts3-4. Synthesis, chemical physical properties of metal nanoparticles are currently of considerable interest because of their potential application in commercial industries. Owing to the small size of the building block and high surface - volume ratio, these material are expected to demonstrate unique properties.

Synthesis of Nano material has grained importance in the field of synthetic technology, In this work has follow Wet chemical route, because of its faster, cleaner and cost effectiveness than all other methods.

In the present work various molar concentration of

Silver-Cadmium Sulphide nanoparticles were synthesized using PVA as a capping agent. It play important role to control the size of particles and has characterized for their size by using X-ray diffraction. The morphology of sample were determined by Scanning electron microscope, FT-IR, EDAX and Transmission electron microscope. On the observation of XRD to assume the size of nanoparticles, it shows between 1-10 nm.

EXPERIMENT


Calculated amount of various molecular ratio of cadmium acetate(X) and silver nitrate(Y) were dissolved in a beaker containing 50ml of de-ionized water and 50 ml of methanol. The above mixture was kept in a magnetic stirrer for stirring, in the mixture a magnetic pallet was added and simultaneously weighted composition of sodium sulphide (Z) dissolved in 50 ml of deionized water and 50 ml of methanol along with

Full Paper 🛥

0.5 gm. of poly vinyl alcohol (PVA)after complete mixing is taken in a burette and contents of the burette were added in to the mixture drop by drop. The stirring were continued for almost half an hour until the fine precipitate of silver doped cadmium sulphide nanoparticle was obtain. And then the mixture was placed in domestic microwave oven for 3-5 mints. The precipitate were then filtered off and washed several times with methanol

 TABLE 1 : Gives detail about Molecular ratio of chemical in this synthesis

S. No.	Sample Code	X gm. Of Cd(COOH)2	Y gm. Of AgNO3	Z gm. Of Na2S
1.	S 1	7.1	1.3	1.6
2.	S2	6.3	1.9	1.8
3.	S 3	6.4	2.2	1.4
4.	S4	6.5	2.3	1.2
5.	S5	6.1	1.9	2.0



in order to get purity of the sample. Various composition of NP's prepared with different molecular ratio.






Figure 1 : Indicates the nanoparticles size between 1-10 nanometer







(c)

2Mm

0034 21/FEB/14

Figure 2 : a, b, c and d shows the morphology of NP's.

Aano Soience and Aano Technology Au Iudiau Journal


X6,500


20kU



Molecular ratio table was shown below.

All the green colored Ag doped CdS powders obtained were subjected to x-ray diffraction using Xray diffractometer. Surface morphology of the samples has been studied using scanning electron microscope








Figure 2 : e, f and g shows the morphology and Surface activity of NP's

(SEM), transmitted electron microscope (TEM) with EDAX is carried out for the elemental analysis of prepared samples and FTIR spectrum of the nanoparticles were recorded.

RESULT AND DISCUSSION

X-ray diffraction analysis

X-ray diffraction pattern of silver doped cadmium sulphide nanoparticles with various compositions shows line broadening of diffraction peaks gives an indication that the synthesized particles are in nanometer's size. The presence silver doped cadmium sulphide nanoparticles in the formation of Bragg's peaks at 2θ values of 12.64, 11.22, and 26.50. The mean diameter of NP's was calculated from the Scherrer formula d=0.94 $\lambda/\beta \cos \theta$, where d is the mean diameter, λ is the wave length of X-ray radiation source of the particle size between 1-10 nm and it can be calculated using Debye-Scherre formula. From XRD data, observed. Ag doped CdS denotes different 20 were 12.640, 11.22, 26.50 and β is the angular full width at half maximum of the XRD peak at half maximum of the XRD peak at diffraction angle θ . The mean diameter was determined to be 1-10nm.

SEM and TEM analysis

The SEM and TEM analysis was explained the morphology and grain size of nano particles. The shape and size of silver doped cadmium sulphide is entirely different from un doped cadmium sulphide. From the




Figure 2 : h. indicates the morphology and unit cell arrangement of NP's




Figure 3 : Shows the nanoparticle with different size

Figure indicates the size between 1-10 nm and morphology was globular in shape, which was entirely different from undoped cadmium sulphide.

FTIR analysis


The Figure 3 Shows the IR spectrum of silver doped cadmium sulphide confirmed peaks at 3128 cm-1 to 3140 cm-1 was assigned to O-H stretching of absorbed water on the surface of CdS. The stretching vibrational peak at 663 to 613 cm-1 indicates the presence of cadmium sulphide. The major peak at 1614, 1402,623

Aano Solence and Aano Technology An Indian Journal were due to the presence of different bands of silver doped cadmium sulphide nanoparticles.

EDAX analysis

The EDAX stands for Energy dispersive X-ray analysis. The EDAX technique were used for elemental analysis or chemical characterization of a sample. From the Figure 4.a and 4.b. shows clearly presence of silver(Ag),Cadmium (Cd) and Sulphide(S). The technique was helped to confirmed the particles presence in this analysis.

5






Figure 4 : a and b EDAX diagram of Ag-CdS

CONCLUSION

The present study indicates that the wet chemical method can be successfully employed for the preparation of silver doped cadmium sulphide nanoparticles. The X-ray diffraction measurement confirms the structure and particle size of the sample was 1-10nm. The scanning electron microscope and transmitted electron microscope image clearly indicates the formation of nano particles with globular shape. Analysis of EDAX confirms that the sample with clear peaks of Cadmium (Cd), Sulphur(S) and Silver (Ag) is around the nominal composition. FTIR shows clearly about the effect of capping agent presents in the mixture. The wet chemical method of synthesis of Ag-CdS NP's using poly vinyl chloride as capping agent with various molecular ratio reported in this work is simple and feasible for production of nano sized particles.

ACKNOWLEDGMENT

The authors are grateful to department of chemistry, Muthurangam arts and science college, Vellore. We would also like to acknowledge SAIF, Research and Development, North-East Hill University, Megalaya. We would thanks to VIT University, Vellore for XRD and IR spectral studies.

REFERENCES

- A.P.Alivisatos; Semiconductor clusters, nanocrystals and quantum dot.science, 271(5251), 933-37 (1996).
- [2] G.Schmid, (Ed.), Clusters and colloids VCH press, New York, (1994).
- [3] S.A.Majetich, Y.Jin; Magnetization direction of

NSNTAIJ, 10(1) 2016

Full Paper

individual Nanoparticles.Science, **284(5413)**, 470-73 (**1999**).

- [4] C.B.Murray, C.R.Kagan, M.G.Bawendi; Selforganization of CdSe.
- [5] B.Srinivasa Rao, B.Rajesh kumar, G.Venkatachalapathi, V.Rajagopal Reddy, T.Subba Rao; 8(2), 53-58 (2011).
- [6] A.P.Alivistoas, Science, 217, 933 (1996).
- [7] Y.P.Sun, J.E.Riggs; Int.Rev.Phys.chem, 18, 43 (1999).
- [8] W.Jia, E.P.Douglas, F.Guo, W.Ji; Appl.Phys.Lett., 85, 6326 (2004).
- [9] R.Heitz, A.Hoffmann, I.Broser; Phys.Rev., 348, 8672 (1993).
- [10] I.Robel, M.Kuno, P.V.Kamat; J.Am.Chem.Soc., 129, 4136 (2007).
- [11] I.Robel, V.Subramanian, M.Kuno, P.V.Kamat, J.Am.Chem.soc., 128, 2385 (2006).
- [12] K.Jacinth Mispa, P.Subramaniam, R.Murugasan; Chalcogenide Letters, 7, 335-340 (2010).
- [13] T.Fukumura, Y. Yamada, H.Toyosaki, T.Hasegawa, H.Koinuma, M.Kawasaki; Appl Surf.Sci., 223, 62 (2004).
- [14] Young-II Kim, R.Seshadri; Inorg.Chem., 19, 8437 (2008).
- [15] E.Chikoidze, Y.Dumont, F.Jomard, O.Gorochov; Thin Solid Films, **515**, 8519 (**2007**).
- [16] Nahar Singh, P.Johri, Daya Soni, Rashmi, Sukhvir Singh, S.P.Singh, Prabaht K.Gupta, K.N.Sood, H.Chander; J.Main Group Metal Chem., 30(4), 213–221 (2007).
- [17] Zhang Jun, Yang Yongdong, Xu Baolong, Jiang Feihong, Li Jianping; J.Crystal Growth, 28, 509 (2005).
- [18] C.X.Xu, A.Wei, X.W.Sun, Z.L.Dong; J.Phys. D: Appl.Phys, 39, 690 (2006).
- [19] L.Vayssieres; Adv. Mater, 15, 461 (2003).
- [20] H.K.Yoshida, K.Sato; J.Phys Chem Solids, 64, 1447 (2003).
- [21] Sanjeev Kumar, C.L.Chen, C.L.Dong, Y.K.Ho, J.F.Lee, T.S.Chan, R.Thangavel, T.K.Chen, B.H.Mok, S.M.Rao, M. K.Wu; Room temperature ferromagnetism in Ni doped ZnS nanoparticles, Journal of Alloys and Compounds, 554, 357–362 (2013).
- [22] Pushpendra Kumar, Kedar Singh; Room temperature ferromagnetism in magic-sized Crdoped CdS diluted magnetic semiconducting quantum dots, Journal of Nanoparticle Research, 13, 1613–1620 (2011).
- [23] Sarma, J.Fabian, X.Hu, I.Zutic; Spinelectronics and spin computation, Solid State Communications, 119,

207 **(2001)**.

- [24] D.Amaranatha Reddy, G.Murali, B. Poornaprakash, R.P. Vijayalakshmi, B.K.Reddy; Structural, optica land magnetic properties of Zn0.97_xCuxCr0.03S nanoparticles, Applied Surface Science, 258, 5206– 5211 (2012).
- [25] Amaranatha Reddy, S.Sambasivam, G.Murali, B.Poornaprakash, R.P.Vijayalakshmi, Y.Aparna, B.K.Reddy, J.L.Rao; Effect of Mnco- doping on the structural, optical and magnetic properties of ZnS:Cr nanoparticles, Journal of Alloys and Compounds, [14] Fengchun, 537, 208–215 (2012).
- [26] Hu, QinghuaLiu, Zhihu Sun, TaoYao, Zhiyun Pan, Yuanyuan Li, JingfuHe, BoHe, ZhiXie, WenshengYan, Shiqiang Wei; Cu and Co codoping effects on room-temperature ferromagnetism of (Co,Cu):ZnO dilute magnetic semiconductors, Journal of Applied Physics, 109, 103705–103708 (2011).
- [27] Xiaohu Huang, Guanghai Li, Lei Duan, Liang Li, Xincun Dou, Lide Zhang; Formation of ZnO nanosheets with room-temperature ferromagnetism by co-doping with Mn and Ni, Scripta Materialia, 60, 984–987 (2009).
- [28] Xinlong Tian, Zhanchang Pan, Huangchu Zhang, Hong Fan, Xiangfu Zeng, Chumin Xiao, GuanghuiHu, Zhigang Wei; Growth and characterization of the Al-doped and Al–Sn codoped ZnO nanostructures, CeramicsInternationa, 139, 6497–6502 (2013).
- [29] C.W. Zou, L.X.Shao, L.P.Guo, D.J.Fu, T.W.Kang; Ferromagnetism and ferroelectric properties of (Mn,Li) co-doped ZnO nanorods arrays deposited by electrodeposition, Journal of Crystal Growth, 331, 44–48 (2011).
- [30] Mingpeng Yu, Hong Qiu, Xiaobai Chen, Hui Li, Wei Gong; Aland Ni co-doped ZnO films with room temperature ferromagnetism, low resistivity and high transparence, Materials Chemistry and Physics, 126, 797–803 (2011).
- [31] X.C.Liu, E.W.Shi, Z.Z.Chen, H.W.Zhang, B.Xiao, L.X.Song; High- temperature ferromagnetismin (Co,Al)-codoped ZnO powders, Applied Physics Letters, 88, 252503–252505 (2006).
- [32] Guangqing Pei, Changtai Xia, Feng Wu, Jun Xu; Absenceofroom- temperature ferromagnetismin Alcodoped Zn0.95 Co0.05 O nanoparticles, Journal of Alloys and Compounds, 467, 539–542 (2009).
- [33] Xingzhi Ning, XiaoF ang Liu, Ronghai Yu, JiShi, Yoshio Nakamura; Materials Transactions, 51, 557– 560 (2010).

6