ISSN : 0974 - 7486

Volume 10 Issue 3



Materials

Science An Indian Journal FUII Paper

MSAIJ, 10(3), 2014 [116-123]

Novel cationic gemini surfactants with different chain length as corrosion inhibitors for carbon steel in 1 M HCl

M.I.Nessim, O.A.A Elshamy, O.H.Abdelraheem*, M.M.Osman Analysis and Evaluation Department, Egyptian Petroleum Research Institute (EPRI), 1, Ahmed El- Zomor St., Nasr City 11727 Cairo, (EGYPT) E-mail : omnia_hassan55@yahoo.com

ABSTRACT

Three cationic gemini surfactants of the type N²,N³-dialkyl-N²,N²,N³,N³tetramethylbutane diamminium bromide namely Ia, Ib and Ic have been synthesized. Their chemical structures were elucidated by the routine methodologies ¹H-NMR, elemental analysis and mass spectroscopy. The surface active properties were examined and found to be influenced by the chemical structure of the surfactants. The synthesized cationic gemini surfactants were tested as corrosion inhibitors for pipeline carbon steel API X52 immersed in 1 M HCl solution, using weight loss method. The obtained data refer to very good inhibitive efficiencies vary with concentrations, and increase in the following order: Ia >Ib > Ic. The Quantum chemical parameters such as highest occupied molecular orbital (HOMO), lowest unoccupied molecular orbital (LUMO) energy levels, energy gap $(E_{HOMO}-E_{LUMO})$, the dipole moment and charge densities were calculated. The theoretical calculations were in good agreement with corrosion inhibition results. © 2014 Trade Science Inc. - INDIA

INTRODUCTION

The application of surfactants as corrosion inhibitors has been studied extensively^[11]. Dimeric (gemini) surfactants are kind of surfactants made up of two identical amphiphilic moieties connected to the level of the head groups by a spacer group, rather than one hydrophilic group and one hydrophobic group for conventional surfactants^[2-5]. Indeed, they offer some advantages, such as lower micelle concentration (CMC), higher surface activity and better wetting properties than the corresponding monomeric surfactants^[6-11].Owing to these unique properties, gemini surfactants have been widely used in industrial detergency, gelation of organic solvents, template synthesis of various materials, etc,^[12,13]. Therefore, investigation on gemini surfactants is still an attractive subject for research. Considerable efforts have been made to design surfactants, and most of them have been focused on the effect of spacer length or its flexibility and hydophobicity^[14,15]. In order to evaluate compounds as corrosion inhibitors and to design novel inhibitors, much more research works were concentrated on the studies of the relationship between structural characteristics of the organic compounds and their inhibiting effects^[16].

Quantum chemical methods have already proven

KEYWORDS

Gemini surfactants; Corrosion inhibition; Carbon steel; Weight loss; Surface activities; Quantum chemical parameters. to be very useful in determining the molecular structure are as well as elucidating the electronic structure and reactivity. Thus, it has become a common practice to carry out quantum chemical calculations in corrosion inhibition studies. The concept of assessing the efficiency of a corrosion inhibitor with the help of computational chemistry is to search for compounds with desired properties using chemical intuition and experience into a mathematically quantified and computerized form^[17,18].

The first goal of this work was to design a series of N^2 , N^3 -dialkyl- N^2 , N^2 , N^3 , N^3 -tetramethylbutane diamminium bromide cationic gemini surfactants, featured with a branched spacer and to investigate their surface activity properties. The second one is to study the inhibitive effect of these surfactants as corrosion inhibitors for carbon steel in 1 M HCl and discussing the results in the light of the theoretical quantum chemical calculations.

EXPERIMENTAL METHODS AND MATERIALS

Synthesis

A series of cationic gemini surfactants of the type N²,N³-dialkyl-N²,N²,N3,N³-tetramethylbutane diaminium bromide namely as Ia, Ib and Ic; (where the alkyl group is dodecyl-, tetradecyl- and hexadecyl- respectively) were synthesized. A mixture of 2,3dibromobutane (0.05)mole) and N.Ndimethylalkylamine (0.0625 mol), is heated in absolute ethanol under reflux for 24 hours, then ethanol is evaporated using the rotary evaporating system. the product was waxy white (due to the presence of the amine in excess). The excess amine was removed by extraction with a mixture of ether-benzene, and finally by an extraction with hexane.

The resulting pure product was recrystallized in pure acetone. The resulting products were confirmed by el-

emental analysis (TABLE 1), ¹H-NMR (TABLE 2) and mass spectroscopy (TABLE 3a,b,c).. The molecular structure of compounds is shown in Figure 1, where n equals (9,11,13) for Ia, Ib, Ic respectively.

TABLE 2: ¹ H-NMR	spectroscopy of Ia, Ib and Ic
-----------------------------	-------------------------------

Type of proton	Chemical Shift (δ) ppm	Spin multiplicity
а	3.88	Quartet
b	3.44	Singlet
с	3.32	Triplet
d	2.09	Multiplet
e	1.66	Doublet
f	1.22	Multiplet
g	0.86	Triplet

m/z	Molecular Formula	m/z	Molecular formula
42	$C_{32}H_{70}Br_2N_2]^{3+.}$	253	$C_{16}H_{33}N_2]^{3+.}$
482	$C_{32}H_{70}N_2]^{3+.}$	211	$C_{14}H_{29}N]^{2+.}$
467	$C_{31}H_{67}N_2]^{3+.}$	98	$C_6 H_{12} N]^{2+.}$
452	$C_{30}H_{64}N_2]^{3+.}$	43	$C_2H_5N]^{2+.}$
283	$C_{18}H_{39}N_2]^{3+.}$	29	CH_2N] ^{2+.}
268	$C_{17}H_{36}N_2]^{3+.}$		

m/z	Molecular Formula	m/z	Molecular formula
698	$C_{36}H_{78}Br_2N_2]^{3+.}$	283	$C_{18}H_{37}N_2]^{3+.}$
538	$C_{36}H_{78}N_2]^{3+.}$	241	$C_{16}H_{25}N]^{2+.}$
525	$C_{35}H_{75}N_2]^{3+.}$	98	$C_6 H_{12} N$] ^{2+.}
510	$C_{34}H_{72}N_2]^{3+.}$	43	$C_2H_5N]^{2+.}$
313	$C_{20}H_{43}N_2]^{3+.}$	29	CH_2N] ^{2+.}
298	$C_{19}H_{40}N_2\big]^{3+.}$		

Measurement of surface tension

The surface tension, at air/liquid interface, of the three synthesized cationic gemini surfactants was determined at 35°C, measured using De-Nouy Tensiometer (Kruss K6 type) which calibrated against distilled water (specific conductivity 1.1×10^{-6} ohm⁻¹ cm⁻¹ at 30

Element %	С	%	Н	%	Bı	:%	N	%
Surfactant	Calc.	Obs.	Calc.	Obs.	Calc.	Obs.	Calc.	Obs.
Ia	59.81	59.58	10.90	10.72	24.92	24.95	4.36	4.75
Ib	61.87	61.85	11.25	11.40	22.89	22.67	4.01	4.08
Ic	63.64	63.45	11.48	11.52	21.17	21.36	3.71	3.65

TABLE 1 : Elemental analysis of compounds Ia, Ib and Ic

Full Paper

m/z	Molecular Formula	m/z	Molecular formula
754	$C_{40}H_{86}Br_2N_2]^{3+.}$	309	$C_{20}H_{41}N_2]^{3+.}$
594	$C_{40}H_{86}N_2]^{3+.}$	267	$C_{18}H_{37}N]^{2+.}$
579	$C_{39}H_{83}N_2]^{3+.}$	98	$C_6 H_{12} N]^{2+.}$
564	$C_{38}H_{80}N_2]^{3+.}$	43	$C_2H_5N]^{2+.}$
339	$C_{22}H_{47}N_2]^{3+.}$	29	CH_2N] ^{2+.}
324	$C_{21}H_{44}N_2]^{3+.}$		

plotting the surface tension in mN m⁻¹, versus log concentration as shown in Figure 2. The abrupt change in the linear line was taken as a critical micelle concentration. The CMC values together with other surface parameters are listed in TABLE 4. By careful inspection CMC decreases as the hydrophobicity increases.

The surface excess concentration $\Gamma_{\text{max}} \pmod{/\text{cm}^2}$ by applying Gibbs equation^[20].




Figure 1 : Molecular structure of synthesized cationic gemini surfactants

°C)^[19]. Freshly prepared aqueous solution of the surfactants (Ia, Ib and Ic), in deionized water was prepared with a concentration range 0.01-10 mmol/L.

Weight loss measurements

Specimens of low carbon steel with dimensions (1cm x 1cm x 0.5cm) were used. Carbon steel grade is (API 5L X52M PSL2) with chemical composition C: 0.28%, Si:0.24%, Mn:1.24%, P: 0.013%, Cr: 0.02%, Ni: 0.02%, Al: 0.03% and the rest is Fe. Prior to immersion, the specimens were abraded in sequence using emery papers of grade number 220, 320, 400, 600, 800, 1000 and 1200. The samples were allowed to stand for 72 hr in 1M HCl solution in the absence and presence of different concentrations of inhibitors ranged from $4x10^{-5}$ to $4x10^{-3}$ mol.1⁻¹. All tests are run in duplicate and the calculated weight losses are avaraged.

Quantum chemical calculations

Quantum mechanical program Chem Bio Draw Ultra 12, was used for molecular modeling. The calculations were based on Ab initio (HF/3-21G and MP2/ 3-21G) and semiemperical (MNDO, AM1 and PM3) methods.

RESULTS AND DISCUSSION

Surface properties

The critical micelle concentrations CMC of the investigated surfactants were determined at 35°C by

Materials Science An Indian Journal




Figure 2 : Variation of surface tension with log C: (▲%) Ia; (o) Ib; and (□%) Ic.

TABLE 4 : Surface properties of the synthesized geminisurfactants

Surfactants	T °C	CMC x 10 ⁴	$\begin{array}{c} \Gamma_{max} x \\ 10^{10} \end{array}$	A _{min}	π
Ia	35	4.89	1.83	0.91	34.50
Ib	35	4.47	3.75	0.44	30.50
Ic	35	3.16	4.24	0.39	28.50
1		dy			

$$\Gamma_{\max} = -\frac{1}{2.303nRT} \frac{dr}{dlogC}$$
(1)

Where R is the gas constant (8.314 J/mol) and T is the absolute temperature. The constant n takes value equals 2 for an ionic surfactants, were the surfactant ion and the counter ion are univalent, and n=3 for a dimeric surfactant made up of divalent surfactant ion and two univalent counter ions, in absence of swamping electrolyte^[21].

The Γ_{max} values in TABLE 4 were used to calculate the minimum area per molecule, A_{min} in Å²/molecule at



the aqueous phase interface using the relationship:

$$A_{\min} = \frac{10^{16}}{N_4 \Gamma_{max}}$$
(2)

Where, N_A : Avogadro 's number, 6.023 x 10²³. There was slight increase in Γ_{max} and decrease in A_{min} by increase in the hydrophobic chain length which might caused from increasing van der Vaals interaction. The effectiveness (π_{cmc}), which indicate the surface activity of the surfactants molecules at their CMCs were determined. The effectiveness in surface tension reduction (π_{cmc}) of the prepared surfactants at 35 °C revealed that Ia has the higher value.

Weight loss measurements

The inhibition efficiency E%. was determined by the following equation^[22]:

 $\theta = 1 - (\Delta Wi / \Delta W_{o})$ (3) E % = 1 - (\Delta Wi / \Delta W_{o}) x 100 (4)

Where E% is the corrosion inhibition efficiency, θ is coverage of the metal surface and ΔW_0 and ΔW_1 are the weight loss per unit area in absence and presence of inhibitors respectively. The results listed in TABLE 5. The plotting of surface coverage (θ) against log C illustrated in Figure 4. The corrosion rate is a concentration dependent, where efficiency (E%) increases with increasing inhibitors concentration and reaches the maximum value near CMC. The inhibition efficiency found to be ranked as follows, Ia> Ib > Ic. It means that the efficiency decreases by increasing the tail chain length of the synthesized gemini surfactants with branched spacer.




Figure 3 : Variation of the inhibition efficiency of carbon steel in the presence of different concentrations of the inhibitors

TABLE 5 : The corrosion inhibition and surface coverage of carbon steel in 1 M HCl with addition of surfactants Ia, Ib and Ic

Surfactants	Conc. (mol.l ⁻¹)	θ	Е %
	4x10 ⁻⁵	0.9780	97.80
	1×10^{-4}	0.9910	99.10
	$2x10^{-4}$	0.9910	99.10
	$3x10^{-4}$	0.9910	99.10
Ia	$4 x 10^{-4}$	0.9970	99.70
	8×10^{-4}	0.9970	99.70
	1×10^{-3}	0.9940	99.40
	$2x10^{-3}$	0.9970	99.70
	$4x10^{-3}$	0.9970	99.70
	$4x10^{-5}$	0.9630	96.30
	1×10^{-4}	0.9791	97.91
	$2x10^{-4}$	0.9793	97.93
Ib	$3x10^{-4}$	0.9796	97.96
	4×10^{-4}	0.9818	98.18
	8×10^{-4}	0.9818	98.18
	1×10^{-3}	0.9827	98.27
	$2x10^{-3}$	0.9875	98.75
	$4x10^{-3}$	0.9895	98.95
	$4x10^{-5}$	0.9650	96.50
	1×10^{-4}	0.9759	97.59
Ic	$2x10^{-4}$	0.9771	97.71
	$3x10^{-4}$	0.9760	97.60
	4×10^{-4}	0.9792	97.92
	8x10 ⁻⁴	0.9750	97.50
	1×10^{-3}	0.9844	98.44
	$2x10^{-3}$	0.9830	98.30
	$4x10^{-3}$	0.9800	98.00




Figure 4 : Langmuir isotherm plots for carbon steel in 1M HCl at presence of different concentrations of cationic gemini surfactants Ia, Ib and Ic.



MSAIJ, 10(3) 2014

Full Paper

The inhibitors having θ near unity, is indicating almost a full coverage of the metal surface with adsorbed surfactant molecules as a good physical barrier shielding the corroding surface from the corrosive medium. From surface activity measurements (TABLE 4), the greatest effectiveness in surface tension reduction (π_{cmc}) was achieved by Ia compared with that obtained by the other two surfactants, which may explain the highest inhibition efficiency achieved by Ia.

Adsorption isotherm

The inhibition efficiency has been found to be closely related to inhibitor adsorption abilities and molecular properties for different kinds of organic compounds^[23]. In order to determine the adsorption mode, various isotherms were tested and by far the best fit was obtained with the Langmuir isotherm Figure 4. by the following relation^[24]:

$$\frac{C}{\theta} = \frac{1}{K} + C \tag{5}$$

TABLE 6. shows the parameters and the regression factor calculated from Langmuir adsorption isotherm. All correlation coefficients (r^2) exceeded 0.99 indicates that the corrosion inhibition of carbon steel by the prepared cationic gemini surfactants was attributed to adsorption of these compounds on the metal surface. However, the slopes of the *C*/ θ versus *C* plots show a little deviation from unity, This deviation may be

 TABLE 6 : Adsorption parameters of inhibitors surfactants
 on the steel surface.

Surfactant	Linear correlation coefficient, r ²	slope	K _{ads} (l. mol ⁻¹)
Ia	0.9999	1.0028	98.3768 x 10 ⁴
Ib	0.9999	1.0110	37.6685 x 10 ⁴
Ic	0.9999	1.0183	90.0556 x 10 ⁴

explained on the basis of interaction between the adsorbed species on the metal surface by mutual repulsion or attraction^[25].

High values of the adsorption constant K can be reasoned for better adsorption and high inhibition efficiency^[26], which is consistent with data obtained from weight loss investigations.

Quantum chemical calculations

Using the Ab initio (HF/3-21G and MP2/3-21G) and semiempirical (AM1, MNDO and PM3) methods of calculations by Chem Bio Draw Ultra 12 software, the Huckel and Mulliken charges, the dipole moments, E_{HOMO} (the highest occupied molecular orbital) and E_{LUMO} (the lowest unoccupied molecular orbital) values were calculated. The charges representative atoms and other relevant quantum parameters were listed in TABLES 7,8 and 9. The optimized structure of the molecules and the electric/orbital density distributions of HOMO and LUMO illustrated in Figure 5 and Figure 6 respectively.

Mulliken population analysis is mostly used for the calculation of the charge distribution in a molecule^[27]. These numerical quantities are easy to obtain and they provide at least a qualitative understanding of the structure and reactivity of molecules^[28]. Furthermore, atomic charges are used for the description of the molecular polarity of molecules. By careful examination of TABLES 7,8 and 9, it found that the values of the electronegative charges of the *N*13, *N*15, *N*16, *N*17, *N*18, and *N*20, were irrelevant to the inhibition efficiency. These results suggested that the adsorptions might not be attributed to a chemical bond between the electronegative atoms and the metal surface.

The dipole moment (μ) values were founded to be increased by the increase in the hydrophobic chain

Quantum parameters	HF(3-21G)	MP2(3-21G)	AM1	MNDO	PM3
$E_{\rm HOMO}~({\rm eV})$	23.790	23.778	23.776	23.783	23.781
$E_{\rm LUMO}~({\rm eV})$	25.736	25.741	25.740	25.741	25.739
$E_{\text{LUMO-HOMO}} (\text{eV})$	01.946	01.963	01.964	01.958	01.958
Huckel charge (eV)	$N_{13} = 0.4906$ $N_{16} = 0.4867$	$N_{13} = 0.4915$ $N_{16} = 0.4871$	$N_{13} = 0.4907$ $N_{16} = 0.4864$	$N_{13} = 0.4908$ $N_{16} = 0.4868$	$N_{13} = 0.4910$ $N_{16} = 0.4873$
Mulliken charge (eV)	$N_{13} = -0.7385$ $N_{16} = -0.7390$	$N_{13} = -0.7423$ $N_{16} = -0.7395$	$N_{13} = 0.0191$ $N_{16} = 0.0301$	$N_{13} = -0.1068$ $N_{16} = -0.0979$	$N_{13} = 0.5958$ $N_{16} = 0.6185$
μ (Debye)	29.67	29.47	29.97	31.03	30.33

TABLE 7 : Quantum Chemical Parameters of Ia

Materials Science An Indian Journal

121

Quantum parameters	HF(3-21G)	MP2/3-21G	AM1	MNDO	PM3		
$E_{\rm HOMO}~({\rm eV})$	23.778	23.778	23.779	23.780	23.784		
$E_{\rm LUMO} ({\rm eV})$	25.737	25.739	25.747	25.746	25.745		
$E_{\text{LUMO-HOMO}} (\text{eV})$	1.959	01.961	1.968	1.966	1.961		
Huckel charge (ev)	$N_{15} = 0.4913$ $N_{18} = 0.4877$	$N_{15} = 0.4912$ $N_{18} = 0.4872$	$\begin{array}{l} N_{15} = 0.5542 \\ N_{18} = 0.6502 \end{array}$	$N_{15} = 0.4912$ $N_{18} = 0.4876$	$N_{15} = 0.4574$ $N_{18} = 0.4926$		
Mulliken charge(ev)	$N_{15} = -0.7398$ $N_{18} = -0.7403$	$N_{15} = -0.7424$ $N_{13} = -0.7379$	$N_{15} = 0.0179$ $N_{18} = 0.0304$	$N_{15} = -0.1068$ $N_{18} = -0.0983$	$N_{15} = 0.5587$ $N_{18} = 0.5857$		
μ (Debye)	36.74	36.71	36.99	38.17	37.59		

TABLE 8 : Quantum chemical parameters of Ib

TABLE 9 : Quantum chemical parameters of Ic

Quantum parameters	HF(3-21G)	MP2/3-21G	AM1	MNDO	PM3
$E_{\rm HOMO}~({\rm eV})$	23.774	23.774	23.760	23.767	23.778
$E_{\rm LUMO}~({\rm eV})$	25.739	25.743	25.734	25.741	25.746
$E_{\text{LUMO-HOMO}} (\text{eV})$	1.965	1.969	1.974	1.974	1.968
Huckel charge (eV)	$N_{17} = 0.4906$ $N_{20} = 0.4874$	$\begin{array}{l} N_{17} = 0.4857 \\ N_{20} = 0.4746 \end{array}$	$N_{17} = 0.4904$ $N_{20} = 0.4874$	$N_{17} = 0.4904$ $N_{20} = 0.4871$	$N_{17} = 0.4526$ $N_{2\setminus 0} = 0.4921$
Mulliken charge (eV)	$N_{17} = -0.7396$ $N_{20} = -0.7103$	$N_{17} = -0.7411$ $N_{20} = -0.7378$	$N_{17} = -0.0191$ $N_{20} = -0.0302$	$\begin{array}{l} N_{17}=\text{-}0.1068 \\ N_{20}=\text{-}0.0978 \end{array}$	$\begin{split} N_{17} &= 0.5581 \\ N_{20} &= 0.5843 \end{split}$
μ (Debye)	43.93	44.36	44.35	45.43	44.87




Figure 5 : Optimized structure of the synthesized cationic gemini surfactants of the type N²,N³-dialkyl-N²,N²,N³,N³-tetramethylbutane diamminium bromide: (a) Ia; (b) Ib; (c) Ic

length. It may indicated that the adsorptions might not be arisen from intermolecular electrostatic force^[16]. Highest occupied molecular orbital energy (E_{HOMO}) and lowest unoccupied molecular orbital energy (E_{LUMO}) are very popular quantum chemical parameters. These orbitals, also called the frontier orbitals, determine the way the molecule interacts with other species. The HOMO is the orbital that could act as an electron donor, since it is the outermost (highest energy) orbital containing electrons. The LUMO is the orbital that could act as the electron acceptor, since it is the innermost (lowest energy) orbital that has room to accept electrons. According to the frontier molecular orbital theory, the formation of a transition state is due to an interaction between the frontier orbitals (HOMO and LUMO) of reactants^[29].

From TABLES 6, 7 and 8 it is found that the $E_{\rm HOMO}$ and the $E_{\rm LUMO}$ changed rulelessly, while the energy gap $E_{\rm LUMO}$ - $E_{\rm HOMO}$; the difference in energy between the $E_{\rm HOMO}$ and $E_{\rm LUMO}$ decreased with increasing the inhibition efficiency. The energy gap (ΔE) is an important stability index^[30]. A large HOMO–LUMO gap implies high stability for the molecule in chemical reactions^[31]

The values of (ΔE) indicates remarkably that the smaller energy gap results in a high corrosion inhibition, reflecting the stronger interaction between the inhibitors and metal surface. The interactions are probably physical adsorption^[32,34].




Figure 6 : The frontier molecule orbital density distributions of the prepared three cationic gemini surfactants of the type N²,N³-dialkyl-N²,N²,N³,N³-tetramethylbutane diamminium bromide: (a) Ia; (b) Ib; (c) Ic.




Figure 7 : Correlations between experimental %E and calculated quantum chemical parameter (ΔE).

An attempt to search correlations among the experimentally obtained inhibition efficiency results and theoretically calculated quantum parameter; energy gap (ΔE) values; are illustrated in Figure 7. The plotting



123

shows that the best correlation obtained using semi empirical methods MNDO and AM1. This result is in accordance with other works^[18,23,35,36].

CONCLUSIONS

Novel synthesized cationic gemini surfactants featured with a branched spacer, showed good inhibition properties for the corrosion of pipeline carbon steel API X52 in 1 M HCl solutions, and the inhibition efficiency increased as their concentration increases.

Based on the weight loss measurements, the inhibiting efficiencies of cationic gemini surfactants followed the order of Ia > Ib > Ic, which is the same order of effectivness in surface tension reduction.

The adsorption of studied cationic gemini surfactants on the carbon steel obeyed the Langmuir adsorption isotherm model.

The experimentally obtained inhibition efficiency was correlated with energy gap which is theoretically calculated by quantum chemical calculations. The correlation was well-proportioned suggested the adsorption of synthesized cationic gemini surfactants on the carbon steel was physical adsorption.

REFERENCES

- L.Qiu A.Xie, Y.Shen; Applied Surface Science, 246, 1 (2005).
- [2] L.Grosmaire, M.Chorro, C.Chorro, S.Partyka, R.Zana; Colloid Polym.Sci., 115, 31 (2000).
- [3] R.Zana; Adv.Colloid interface Sci., 97, 205 (2002).
- [4] M.Pisarcik, M.J.Rosen, M.Polakovicova, F.Devinsky, I.Lacko; J.Colloid interface.Sci., 289, 560 (2005).
- [5] Y.X.Wang, Y.C.Han, X.Huang, M.W.Cao, Y.L.Wang; J.Colloid interface Sci., 319, 534 (2008).
- [6] Zana, M.Benrraou, R.Rueff; Lngmuir, 7, 1072 (1991).
- [7] C.Chorro, M.Chorro, O.Dolladille, S.Partyka, R.Zana; J.Colloid interface Sci., 199, 169 (1998).
- [8] R.Oda, I.Huc, S.J.Canadau; Chem.Commun., 2105 (1997).
- [9] F.L.Duivenvoorde, M.C.Feiters, S.J.van der Gaast; J.B.F.N.Engberts, Langmuir, 13, 3737 (1997).
- [10] R.Zana, J.D.Xia; In: R.Zana, J.D.Xia, (Eds.); Gemini Surfactants, Dekker, New York, (2004).

[11] T.Lu, F.Han, G.R.Mao, G.F.Lin, J.B.Huang, X.Huang, Y.L.Wang, H.L.Fu; Langmuir, 23, 2932 (2007).

- [12] S.H.Han, J.Xu, W.G.Hou, X.M.Yu, Y.S.Wang; J.Phys.Chem.B, 108, 15043 (2004).
- [13] T.Lu, Y.Lan, Ch.Liu, J.Huang, Y.Wan; J.Colloid Interface Si., 377, 222 (2012).
- [14] L.Grosmaire, M.Chorro, C.Chorro, S.Partyka, R.Zana, Prog.Colloid.Polym.Sci,.115, 31 (2000).
- [15] L.Grosmaire, M.Chorro, C.Chorro, S.Partyka, S.Lagerge, Thermocheimica Acta, 379, 255 (2001).
- [16] Y.Yan, W.Li, L.Cai, B.Hou; Electrochimica Acta, 53, 5953 (2008).
- [17] E.Kraka, D.Cremer; J.Am.Chem.Soc., 122, 8245 (2000).
- [18] G.Gece; Corrosion Science, 50, 2981 (2008).
- [19] M.J.Rosen, M.L.Baum, F.Kasher; JAOCS, 53, 742 (1976).
- [20] M.J.Rosen; þ þSurfactants and Interfacial phenomena. John Wiley & Sons, New York, (1978).
- [21] E.Alami, S.Abrahmsen-Alami, J.Eastoe, R.K.Heenan; Langmuir, 19, 1821 (2003).
- [22] A.M.Badawi, M.A.Hegazy, A.A.El-Sawy, H.M.Ahmed, W.W.Kamel; Marerials Chemistry and Physics, 124, 458 (2010).
- [23] T.Arslan, F.Kandemirli, E.E.Ebenso, I.Love, H.Alemu; Corrosion Science, 51, 35 (2009).
- [24] A.S.Fouda, A.A.Al-Sarawy, F.Sh.Ahmed; H.M.El-Abbasy Corrosion Science, 51(3), 485 (2009).
- [25] A.A Abdel-Azim, L.A Shalaby, H Abbas; Corros.Sci., 14, 21 (1974).
- [26] M.A.Hegazy; Corrosion Science, 51, 2610 (2009).
- [27] J.N.Murrell, S.F.Kettle, J.M.Tedder; The Chemical Bond, John Wiley & Sons, Chichester, (1985).
- [28] C.Gruber, V.Buss; Chemosphere, 19, 1595 (1989).
- [29] K.Fukui; Theory of Orientation and Stereoselection, Springer-Verlag, New York, (1975).
- [30] D.F.V.Lewis, C.Ioannides, D.V.Parke; Xenobiotica, 24, 401 (1994).
- [31] Z.Zhou, R.G.Parr; J.Am.Chem.Soc., 112, 5720 (1990).
- [32] I.Lukovits, K.Palfi, E.Kalman; Corrosion, 53, 915 (1997).
- [33] M.O[°].Zcan, ÿI.Dehri, Prog.Org.Coat., 51, 181 (2004).
- [34] Y.Yana, W.Li, L.Caia, B.Hou; Electrochimica Acta, 53, 5953 (2008).
- [35] G.Bereket, E.Hûr, C.Öðretir; Journal of molecular Structure (Theochem), 578, 79 (2002).
- [36] I.Ahamad, R.Prasad, M.A.Quraishi; Corrosion Science, 52, 933 (2010).

